

CHRIS NATYNKOWY

PANELE LED


CZ: LED panely/ SK: LED panely/ EN: LED panel



A



B



	INDEX	ABC		Lm	Tc[K]		A [mm]	B [mm]	
A	045609	Chris LED	30 W	100lm/W	4000 K	Biały biła white	400	400	5902808809616
B	045644	Chris LED	30 W	100lm/W	4000 K	Czarny Černá Čierny Black	400	4000	5902808809708

AC 230V	SMD LED	120	
CRI(Ra)	IP		
>80 icon"/>			
>80	40000 h	20	
III	CE	RoHS COMPLIANT	

Materiał / Materiál / Material

PL: aluminium

CZ: hliník

SK: hliník

EN: aluminum

Optymalne warunki eksploatacji:

Optimální provozní podmínky:

Optimálne prevádzkové podmienky:

Optimal operating conditions:

PL: temperatura.: od -25°C to +60°C

wilgotność: <85% ciśnienie: 690-1060 hPa

CZ: teplota: od -25°C do +60°C

vlhkost: <85% tlak: 690-1060 hPa

SK: teplota: od -25°C do +60°C

vlhkost: <85% tlak: 690-1060 hPa

EN: temperature: from -25°C do +60°C

humidity: <85% pressure: 690-1060 hPa

Uwagi / Komentář / Komentáre

PL: Zasilacz w komplecie

CZ: Napájení je součástí dodávky

SK: Napájanie je súčasťou dodávky

EN: Power supply included

BroLux