

# OGIMA

## OPRAWY LED

CZ: LED svítidlo/ SK: LED svetidlo/ EN: LED lamp



INDEX	ABC		Lm	Lm	Tc[K]		A [mm]	B [mm]	C [mm]	
012665	OGIMA	30 W	3300 lm	110 lm/W	4000 K	Biały biłá biely white	1151	36	40	5902216796812
012858	OGIMA	30 W	3300 lm	110 lm/W	4000 K		1151	36	40	5902216796829
012826	OGIMA	40 W	4400 lm	110 lm/W	4000 K		1485	36	40	5902216796836

### Dodatkowe akcesoria



012859 Zestaw linek do powieszenia

AC 230V	SMD LED	90°	
80	IP 20	IK 06	0,9

#### Uwagi / Komentář / Komentáre

PL: Zasilacz w komplecie

CZ: Napájení je součástí dodávky

SK: Napájanie je súčasťou dodávky

EN: Power supply included

#### Materiał / Materiál / Material

PL: tworzywo sztuczne PC, aluminium

CZ: PC plast, hliník

SK: PC plast, hliník

EN: PC plastic, aluminum

#### Optymalne warunki eksploatacji:

Optimální provozní podmínky:

Optimálne prevádzkové podmienky:

Optimal operating conditions:

PL: temperatura.: od -10°C do +25°C

wilgotność: <85% ciśnienie: 690-1060 hPa

CZ: teplota: od -10 ° C do + 25 ° C

vlhkost: <85% tlak: 690-1060 hPa

SK: teplota: od -10 ° C do + 25 ° C

vlhkost: <85% tlak: 690-1060 hPa

EN: temperature: from -10 ° C to + 25 ° C

humidity: <85% pressure: 690-1060 hPa

