



NAŚWIETLACZ LED

CZ: vedl světlomet / SK: vedie svetlomet / EN: LED floodlight

Driver



| INDEX | ABC | | | | | Tc[K] | | A [mm] | B [mm] | C [mm] | |
|--------|------------|--------|-----------|----------|-----|--------|---|--------|--------|--------|---------------|
| 012610 | Paxton LED | 250 W | 35000 lm | 140 lm/W | 25° | 4000 K | | 460 | 300 | 150 | 5902216797017 |
| 012609 | Paxton LED | 360 W | 48600 lm | 135 lm/W | 90° | 4000 K | Czarny Niebieski / Černá Modrá / Čierná Modrá / Black Blue | 300 | 250 | 120 | 5902216797000 |
| 012611 | Paxton LED | 500 W | 67350 lm | 140 lm/W | 90° | 4000 K | | 670 | 300 | 150 | 5902216797024 |
| 012612 | Paxton LED | 720 W | 108000 lm | 150 lm/W | 90° | 4000 K | | 560 | 460 | 150 | 5902216797031 |
| 012613 | Paxton LED | 1000 W | 151200 lm | 140 lm/W | 90° | 4000 K | | 670 | 560 | 200 | 5902216797048 |
| 012614 | Paxton LED | 1440 W | 201600 lm | 140 lm/W | 90° | 4000 K | | 880 | 560 | 200 | 5902216797055 |

Materiał / Materiál / Material

PL: aluminium

CZ: hliník

SK: hliník

EN: aluminum

Uwagi / Komentář / Komentáre

PL: Zasilacz w komplecie

CZ: Napájení je součástí dodávky

SK: Napájanie je súčasťou dodávky

EN: Power supply included

Dostępne Akcesoria:



013382 Soczewka 45°
do Paxton



013383 Soczewka 60°
do Paxton



AC 230V



SMD3030



NON-DIM



>80

IP

65

IK

08



Optymalne warunki eksploatacji:

Optimální provozní podmínky:

Optimálne prevádzkové podmienky:

Optimal operating conditions:

PL: temperatura: od -25°C do +60°C

wilgotność: <85% ciśnienie: 690-1060 hPa

CZ: teplota: od -25°C do +60°C

vlhkost: <85% tlak: 690-1060 hPa

SK: teplota: od -25°C do +60°C

vlhkost: <85% tlak: 690-1060 hPa

EN: temperature: from -25°C to +60°C

humidity: <85% pressure: 690-1060 hPa