









12V,24V PLASTIKOWE IP67

ZASILACZE LED STAŁONAPIĘCIOWE

CZ: Napájecí zdroje s konstantním napětím/ SK: Napájacie zdroje s konštantným napätím/ EN: LED power supply constant voltage



INDEX	 IN	 OUT					 L x W x H	
1541	100-240VAC	12VDC	1,0A	12W	100mVpp	-30°C ÷ +45°C	130×24×21mm	5902216747210
154	100-240VAC	12VDC	1,67A	20W	100mVpp	-30°C ÷ +45°C	138×29×21mm	5902216748446
1542	100-240VAC	12VDC	2,5A	30W	100mVpp	-30°C ÷ +45°C	115×34×26mm	5902216703544
156	100-240VAC	12VDC	3,33A	40W	100mVpp	-30°C ÷ +45°C	145×39×30mm	5902216703551
151	100-240VAC	12VDC	5,0A	60W	120mVpp	-30°C ÷ +45°C	160×40×32mm	5902216703568
127	100-240VAC	12VDC	8,33A	100W	120mVpp	-30°C ÷ +45°C	185×50×36mm	5902216703575
012963	100-240VAC	12VDC	8,33A	100W	120mVpp	-30°C ÷ +45°C	165×42×34mm	5902216799202
009755	100-240VAC	12VDC	1A	12W	100mVpp	-30°C ÷ +45°C	120×26×35mm	5902216703261
009765	100-240VAC	12VDC	1,7A	20W	100mVpp	-30°C ÷ +45°C	118×35×26mm	5902216703292
009782	100-240VAC	12VDC	3,33A	40W	100mVpp	-30°C ÷ +45°C	150×39×30mm	5902216703254
009781	100-240VAC	12VDC	2,5A	30W	100mVpp	-30°C ÷ +45°C	147×40×30mm	5902216703315
009783	100-240VAC	12VDC	5A	60W	120mVpp	-30°C ÷ +45°C	165×42×34mm	5902216703346
001973	100-260VAC	24VDC	0,62A	15W	100mVpp	-30°C ÷ +45°C	36,5x31,5x18,5mm	5902216725218
002981	100-260VAC	24VDC	1,25A	30W	100mVpp	-30°C ÷ +45°C	47x20,5x23mm	5902216725225
001790	100-260VAC	24VDC	2,5A	60W	100mVpp	-30°C ÷ +45°C	47x20,5x23mm	5902216725232

IP 

67 IN&OUT



Materiał / Materiál / Materiál

PL: Tworzywo sztuczne

CZ: Plast

SK: Plast

EN: Plastic